

Product data sheet

Automation technology - Voltage and Power Supply



Product description **M12 Square male panel mount connector, Contacts: 4, unshielded, single wires, IP40, UL**


Area **series 813**

Part no. **76 0939 0115 00044-0200**


Illustration



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	76 0939 0115 00044-0200
Notice	Alternative part no.: 09 0631 070 04 Please note that, due to the change from the old to the new order number, there may be deviations in the technical specifications. For questions about product details, please use the 'Contact Customer Service' form on the right.
Connector design	Square male panel mount connector
Type standard	DIN EN IEC 61076-2-111:2018-10; VDE 0687-76-2-111:2018-10
Wire length	0.2 m (Standard 0.2 m. Other lengths are available on request).
Version	Connector pin straight
Connector locking system	screw
Termination	single wires
Degree of protection	IP40 IP67 with seal, see accessories
Connection cross-section	1.38 mm ² / AWG 16
Temperature range from/to	-40 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	26.81
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	63 V
Rated impulse voltage	1500 V
Rated current	12.0 A
Pollution degree	3

Product data sheet

Automation technology - Voltage and Power Supply



Product description **M12 Square male panel mount connector, Contacts: 4, unshielded, single wires, IP40, UL**
 Area **series 813**
 Part no. **76 0939 0115 00044-0200**

Overvoltage category III
 Insulating material group II
 EMC compliance unshielded

Material

Contact body material PA
 Contact material CuZn (brass)
 Contact plating Au (gold)
 REACH SVHC CAS 7439-92-1 (Lead)
 SCIP number bdc5933-9a2e-47f1-b05f-60769ca803cc
 PFAS present yes


Authorization/approvals

Approvals UL

Classifications

eCl@ss 11.1 27-44-01-09
 ETIM 9.0 EC003569

Assembly instructions / Panel cut-out



Voraussetzungen für Schutzart IP67:


1. Verwendung von Dichtung, Best.-Nr. 16 0959 000
2. Gewinde M3 (4x) als Gewindegewinde oder Schraubenköpfe abgedichtet

Requirements for Degree of protection IP67:

1. Use of sealing, Ordering-No. 16 0959 000
2. M3 thread (4x) sealed as a threaded blind holes or screw heads

Product description **M12 Square male panel mount connector, Contacts: 4, unshielded, single wires, IP40, UL**
Area **series 813**
Part no. **76 0939 0115 00044-0200**

Derating curve



Product description	M12 Square male panel mount connector, Contacts: 4, unshielded, single wires, IP40, UL
Area	series 813
Part no.	76 0939 0115 00044-0200

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).