


|                     |  |
|---------------------|--|
| Product description | <b>M12 Male cable connector - female cable connector M8x1, Contacts: 4, unshielded, moulded on the cable, IP67, UL, PUR, black, 4 x 0.34 mm<sup>2</sup>, 2 m</b> |
| Area                | <b>series 765</b>  |
| Part no.            | <b>77 3429 3406 50004-0200</b>   |


**Illustration**



**Scale drawing**



**Contact arrangement (Plug-in side)**



**Technical data**

**General features**

|          |                                     |
|----------|-------------------------------------|
| Part no. | <b>77 3429 3406 50004-0200</b>      |
|          | Alternative part no.: 79 5009 20 04 |

|                           |  |
|---------------------------|--|
| Notice                    | Please note that, due to the change from the old to the new order number, there may be deviations in the technical specifications. For questions about product details, please use the 'Contact Customer Service' form on the right. |
| Connector design          | Male cable connector - female cable connector M8x1   |
| Type standard             | DIN EN 61076-2-104<br>DIN EN 61076-2-101   |
| Cable length              | 2 m (Standard 1 m and 2 m. Other lengths are available on request.)  |
| Version                   | Connecting cable   |
| Connector locking system  | screw  |
| Termination               | moulded on the cable   |
| Degree of protection      | IP67   |
| Cross-sectional area      | 0.34 mm <sup>2</sup> / AWG 22  |
| Temperature range from/to | -25 °C / 85 °C   |
| Mechanical operation      | > 100 Mating cycles  |
| Weight (g)                | 60.00  |
| Customs tariff number     | 85444290   |
| Country of Origin         | DE   |

**Electrical parameters**

|                           |            |
|---------------------------|------------|
| Rated voltage             | 60 V       |
| Rated impulse voltage     | 800 V      |
| Rated current             | 4.0 A      |
| Pollution degree          | 3          |
| Overvoltage category      | II         |
| Insulating material group | II         |
| EMC compliance            | unshielded |

|                     |  |
|---------------------|--|
| Product description | <b>M12 Male cable connector - female cable connector M8x1, Contacts: 4, unshielded, moulded on the cable, IP67, UL, PUR, black, 4 x 0.34 mm<sup>2</sup>, 2 m</b> |
| Area                | <b>series 765</b>  |
| Part no.            | <b>77 3429 3406 50004-0200</b>   |

## Material

|                       |                                      |
|-----------------------|--------------------------------------|
| Contact body material | PUR                                  |
| Contact material      | CuZn (brass)                         |
| Contact plating       | Au (gold)                            |
| REACH SVHC            | CAS 7439-92-1 (Lead)                 |
| SCIP number           | 75530375-4f50-4cfd-b021-ca1be2b4af92 |

## Authorization/approvals

|           |    |
|-----------|----|
| Approvals | UL |
|-----------|----|

## Classifications

|          |          |
|----------|----------|
| ETIM 9.0 | EC002638 |
|----------|----------|

## Cable data - Structure of the cable

|                        |                          |
|------------------------|--------------------------|
| Cable diameter         | 4.7 mm                   |
| Cross section          | 4 x 0.34 mm <sup>2</sup> |
| Sheath material        | PUR                      |
| Single-lead insulation | PP9Y halogen-free        |
| Single-lead structure  | 42 x 0.10 mm             |
| Cable color            | black                    |

## Cable data - Mechanical properties

|                              |                                       |
|------------------------------|---------------------------------------|
| Bending radius, fixed cable  | ≥ 5 x Ø                               |
| Bending radius, moving cable | ≥ 10 x Ø                              |
| Bending cycles               | > 5 million                           |
| Permitted acceleration       | 5 m/s <sup>2</sup>                    |
| Travel speed                 | ≤ 200 m/min (5 m horizontal distance) |

## Cable data - Thermal properties

|   |                |
|---|----------------|
| Temperature range cable in move from/to | -25 °C / 90 °C |
| Temperature range cable fixed from/to   | -50 °C / 90 °C |

|                     |  |
|---------------------|--|
| Product description | <b>M12 Male cable connector - female cable connector M8x1, Contacts: 4, unshielded, moulded on the cable, IP67, UL, PUR, black, 4 x 0.34 mm<sup>2</sup>, 2 m</b> |
| Area                | <b>series 765</b>  |
| Part no.            | <b>77 3429 3406 50004-0200</b>   |

## Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages. Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).